



**Accurate  
Airflow  
Measurement  
for  
Commercial  
HVAC  
Applications**



PRECISE, RELIABLE, TRUSTED  
**SOLUTIONS**  
IN AIRFLOW MEASUREMENT

- BUILDING AIRFLOW MEASUREMENT AND CONTROL
- ROOM OR SPACE PRESSURIZATION
- OUTSIDE REFERENCE PRESSURE MEASUREMENT
- LABORATORY & HOOD EXHAUST
- OUTDOOR AIRFLOW MONITORING



**Air Monitor**  
Precision Airflow Measurement  
An ONICON Brand



## HVAC APPLICATIONS

**BUILDING AIRFLOW MEASUREMENT AND CONTROL** - The distribution of conditioned air is the primary means of heating and cooling most commercial buildings today. Proper airflow control within a building is not only important for the health and comfort of the building's occupants, it is also important for the health and long term performance and longevity of the building. Accurate airflow measurement allows the HVAC system to work effectively as designed, and efficiently as required to meet ever increasing energy conservation goals. Installations for this application include:

**Ducted Airflow Measurement** - Mechanical duct work is the most common means for distributing the conditioned air throughout most commercial buildings. The duct system provides the best opportunities for accurate airflow measurement due to its controlled dimensions, and the typical obstructions found within a duct system are generally well defined.

**Fan Inlet/Discharge Measurement** - Measuring airflow at the fan inlet presents challenges from a measurement technology stand point. Achieving accurate airflow measurement at the fan inlet, without affecting fan performance, is an important consideration when selecting the correct meter. The large variation in airflow velocity, as well as the multiple fan configurations that exist within an AHU, must be taken into consideration. Measuring airflow at the fan inlet can be advantageous from an accessibility stand point as well as monitoring the performance of fan walls at the source.

**Outdoor Airflow Measurement** - Controlling the amount of outside air entering a building is required to maintain pressurization, meet energy efficiency goals, confirm compliance with local building codes and maintain the health of the building and its occupants. Accurate measurement of outside airflow is required for proper operation of today's high performance buildings. Outside air can pose a significant challenge regarding the metering technology to be selected. Some of the more common challenges associated with outdoor airflow measurement include: low airflow velocities over large operating ranges such as a split - min/max economizer system, blowing dust and debris, and moisture laden air at the point of measurement. Choosing a technology that is impervious to airborne contaminants, can measure low airflow rates, has high turn down capability and one that provides the desired BAS outputs will facilitate a successful installation.

Applications	THERMAL DISPERSION AIRFLOW MEASUREMENT				DIFFERENTIAL PRESSURE		
	Installations	ELECTRA-flo/SD	ELECTRA-flo Probe Array	ELECTRA-flo /FI Fan Inlet Station	FIXED INLET VOLU-flo OAM II Outdoor Airflow Measurement System	STATIC PRESSURE SENSING S.A.P. Static Air Pressure Sensor	S.O.A.P. Static Outdoor Air Pressure Sensor
Building Airflow Measurement and Control	Ducted Airflow	*	*				
	Fan Inlet			*			
	Fan Discharge	*	*				
	Outdoor Airflow Monitoring		*		*		
Building / Space Pressurization	Fan Tracking	*	*	*			
	Outdoor Pressure Reference					*	*
	Room / Space Pressurization					*	
Indoor Air Quality	Outdoor Airflow Monitoring		*		*		
	Laboratory Hood Exhaust Duct	*					





**BUILDING /SPACE PRESSURIZATION** - Proper pressurization of buildings and indoor spaces is a crucial component required for the management of indoor air quality, maximizing energy efficiency and maintaining occupant health and comfort. Lack of control with regard to pressurization can lead to a host of problems including the infiltration of moisture, cold winter or hot summer drafts and doors that are difficult to open or slam shut. Some airflow measurement strategies for this application include:

**Fan Tracking** - Fan tracking is the accurate measurement of the entire airflow system including supply and return air, outside and relief air. Airflow measurement is a much more effective and accurate means of maintaining building pressurization when compared to static pressure measurements made throughout an entire building.

**Outside Reference Pressure Measurement** - Indoor pressures must be measured relative to a reference pressure, usually the outside air pressure.

**Room or Space Pressurization** - This is essential for managing indoor air quality, energy savings and occupant comfort. Prevents unintended pressure levels which can lead to complications for the building systems, the building envelope, and problems between adjacent spaces such as laboratories and hospital rooms.

**INDOOR AIR QUALITY** - Creating and maintaining proper indoor air quality in today's built environment can be a challenging task. The effect that poor indoor air quality has on building occupants can range from loss of efficiency and performance to specific acute health issues. Airborne contaminants found within buildings come from a number of sources including people, processes and the materials used in building construction. Maintaining indoor air quality requires accurate airflow measurement. A few of the typical strategies implemented for this application include:

**Outdoor Airflow Monitoring** - Providing adequate dilution air to the occupied space within a building is the best way to control the level of contamination within the space. Bringing in the right amount of outside air is crucial to maintain proper building operation, meet energy conservation goals, and maintain the IAQ demanded in today's built environment. Accurately and continuously monitoring the outside air flowing into a building will allow the BAS to control the building as designed.

**Laboratory & Hood Exhaust** - Provides essential information to the lab system for maintaining occupant comfort and safety, space pressurization relative to the rest of the building and/or other spaces, and confirms fume hood operation.

DIFFERENTIAL PRESSURE PITOT TUBE VELOCITY PRESSURE AIRFLOW MEASUREMENT				TRANSMITTERS AND MONITORS			
VOLU-probe Pitot Traverse Probe	FAN-E Station	VOLU-probe/FI Fan Inlet Station	Aluminum LO-flo Traverse Station	VELTRON DPT2500-plus	VELTRON II	SENTRY Room Pressurization Monitor	Installations
*	*		*	*	*		Ducted Airflow
		*		*	*		Fan Inlet
*	*			*	*		Fan Discharge
							Outdoor Airflow Monitoring
*	*	*		*	*		Fan Tracking
							Outdoor Pressure Reference
				*	*	*	Room / Space Pressurization
							Outdoor Airflow Monitoring
*(SS)	*			*	*		Laboratory Hood Exhaust Duct



### **ELECTRA-flo Thermal Airflow Measurement System**

- Rugged probes with aerodynamic sensor apertures - Requires less straight run
- Up to 32 individual sensing points per transmitter - More sensing points means better accuracy
- Daisy chain multiple probes per transmitter - Reduces cabling and conduit
- NIST\* traceable calibration - Guaranteed accuracy within  $\pm 2\%$  of actual flow
- ELECTRA-flo G5 Transmitter included - Local display with programming interface, BACnet<sup>®</sup> MS/TP, MODBUS<sup>®</sup> and analog outputs. Optional true dual channel version with duct size, dimension data and sensing point allocation set independently for each channel

### **ELECTRA-flo/SD Thermal Airflow & Temperature Measurement System**

Designed to measure airflow and temperature in small duct variable air volume applications.

- Measure airflow and temperature in 4" - 16" diameter ducts
- Analog outputs for flow and temperature for improved control and efficiency in multi-zone VAV systems
- Optional BACnet or MODBUS RS485

### **ELECTRA-flo/CM Thermal Airflow Measurement Station**

All features of ELECTRA-flo Thermal Airflow Measurement System plus:

- ELECTRA-flo thermal probes mounted in rigid, welded, galvanized casing - Simplifies installation
- Honeycomb cell air straightener - Reduces straight run requirements

### **ELECTRA-flo/FI Thermal Fan Inlet Airflow Probe**

- Dual point thermal dispersion sensor probes mounted in sensor housing - Simplifies installation
- Installs directly in fan inlet with virtually no pressure drop
- ELECTRA-flo G5 Transmitter included

\*National Institute of Standards and Technology





### **VOLU-flo/OAM II Outdoor Airflow Measurement System**

- Robust and reliable construction - Readings are unaffected by wind direction, airborne moisture and dirt
- Factory calibration - Guarantees accuracy within  $\pm 5\%$  of reading
- Measures inlet velocities as low as 100 FPM
- New and retrofit installations onto most single and dual inlet package air handlers
- Local display of data and direct analog interface with BAS for data logging and/or control of outside air dampers
- ASHRAE 62-189.1 compliant

### **OAM II Outdoor Airflow Measurement Uni-Sensor**

- Unaffected by airborne dust and debris and condensing moisture
- Reliable airflow measurement without the need for long straight runs
- Largely immune to effects of shifting wind loads and wind gusts
- The uni-sensor is constructed of 316 stainless steel and is resistant to corrosion caused by salt and most other airborne corrosives
- Uni-Sensors are ideal for retrofit installations because they are easily mounted to a variety of existing inlet types
- Uni-Sensors combine an outside reference (high pressure) sensor and an inlet airflow (low pressure) sensor into one assembly

### **VOLU-flo/OAM II Outdoor Airflow Measurement Station**

- Stainless steel sensors factory mounted directly onto rugged casing - Simplified installation
- Expanded metal provides known fixed inlet flow coefficient - Removes the need for field characterization
- Factory calibrated for selected applications - Guarantees accuracy
- AMCA\* certified - Within  $\pm 5\%$  of actual airflow across specified flow range



\*Air Movement and Control Association

www.airmonitor.com • 800-984-4246



### **VOLU-probe Pitot Airflow Measurement Traverse Probe**

- Multiple Pitot total and static pressure sensing points - Improved accuracy
- Senses average total and static pressure traverses of an air stream
- AMCA\* certified - Within  $\pm 2\%$  certified accuracy

### **VOLU-probe/SS Stainless Steel Airflow Measurement Traverse Probe**

- Ideal for clean or harsh and particulate laden applications
- Temperature range is  $-2^{\circ}\text{F}$  to  $900^{\circ}\text{F}$
- Accurate within  $\pm 2-3\%$  of actual flow



### **VOLU-probe/VS Pitot Airflow Measurement Traverse Station**

- One or more VOLU-probes factory mounted in a rigid, galvanized casing - Simplifies installation
- Senses average total and static pressure traverses of an air stream
- AMCA\* certified - Within  $\pm 2\%$  certified accuracy

### **VOLU-probe/FI Pitot Fan Inlet Airflow Traverse Station**

- Pair of offset traverse probe mounts directly to fan inlet
- Accurately measures inlet velocity pressure and air volume
- Aluminum or stainless



### **FAN-E Pitot Airflow Measurement Traverse Station**

- Multiple Pitot total and static pressure sensing points
- Improved accuracy
- Traverse station includes air straightening honeycomb cell
- Reduces straight run requirements
- AMCA\* certified - Within  $\pm 2\%$  certified accuracy

\*Air Movement and Control Association

www.airmonitor.com • 800-984-4246





### VELTRON DPT 2500-plus Transmitter

- Ultra-low differential pressure and flow transmitter
- Accurate within  $\pm 0.25\%$  of natural span - Ranges from 0.05 to 25.0 in wc
- Ideal for demanding HVAC and process applications
- Microprocessor based configuration and calibration

### VELTRON II "Smart" Transmitter

- Ultra-low differential pressure and flow "smart" transmitter
- Auto zeroing function essentially produces a "self-calibrating" transmitter
- Accurate within  $\pm 0.1\%$  of operational span
- Ideal for the most critical and demanding HVAC and industrial applications



### Aluminum LO-flo Pitot Airflow Measurement Traverse Station

- Measures airflow in small round duct work between 4" - 8"
- Measures volumes between 35 - 1700 CFM
- Accurate within  $\pm 2\%$  of actual airflow

### S.O.A.P. - Static Outdoor Air Pressure Sensor

- Accurate and instantaneous sensing of outside static air pressure levels
- Unaffected by wind direction or gusts




### STATIC PRESSURE PORTS S.A.P. - Static Air Pressure Sensor

- Steady, non-pulsating output of room, space or plenum pressure measurements
- Aluminum or stainless steel construction

### SENTRY Room Pressurization Monitor

- Continuous monitoring and control of the differential pressure or rate of airflow between adjacent spaces - Ideal for laboratories, operating rooms and patient isolation areas



# Any Way The Wind Blows...

## OAM II

The trusted and verified choice for accurate outdoor airflow measurement – essential for operating efficient and healthy buildings



The only system that is both accurate and reliable in challenging Outdoor Airflow Applications!

### Engineered for measuring Outdoor Airflow

- Guaranteed accuracy (+/- 5% of reading) and absolutely reliable, no straight duct run required
- Unaffected by wind, rain and debris

### Broad application capabilities

- Operates accurately from minimum through economizer mode
- Ability to measure two independent inlets with a single system

### Easy implementation

- Analog Output, Native BACnet® MS/TP and Modbus® RTU
- Simple to install on new and retrofit projects

Call today to schedule a demonstration

[airmonitor.com](http://airmonitor.com) • [hvacsales@airmonitor.com](mailto:hvacsales@airmonitor.com)  
1(800)AIRFLOW



**Air Monitor**  
Precision Airflow Measurement  
An ONICON Brand